

We Claim :

1. An alternating current machine comprising a rotor journalled for rotation within a stator comprising stator windings which are gathered together into an annular array at one end of the stator, the stator windings having terminal leads which are guided around respective circumferentially extending paths and coupled to terminal means, there being a plurality of such circumferentially extending paths, each at locations which are spaced axially from other such paths with respect to the stator, the improvement comprising a circumferential array of supporting and guiding means at said one end of the stator for guiding said terminal leads around said paths, the supporting and guiding means being spaced from one another circumferentially such that said terminal leads supported and guided thereby extend between them in free space and ventilation gaps are formed between adjacent terminal leads and supporting and guiding means whereby cooling of the terminal leads is enhanced by air flow through those ventilation gaps.

2. An alternating current machine according to claim 1, wherein each stator winding lead is an integral continuation of a conductor which forms a respective

stator winding.

3. An alternating current machine according to claim 1, wherein the stator winding terminal leads that
5 comprise the ends of a respective stator winding are led together for connection to respective terminals of a terminal block from a location which is in the same notional plane that is normal to the axis of rotation of the rotor within the stator.

10

4. An alternating current machine, according to claims 1, wherein each of the supporting and guiding means of said array comprises an axially orientated member which is formed of electrically insulating plastics material
15 and which is operable to guide the discrete bundles side by side along the respective paths between the adjacent members of the array.

5. An alternating current machine according to claim
20 4, wherein each member comprises an elongate back portion with integral prongs which project laterally therefrom so that it has the form of a comb, the prongs projecting outwardly with respect to the axis of the stator and serving as spacers which space juxtaposed ones of the
25 terminal leads apart and react electromagnetic forces

which act to urge towards them either of the terminal leads they separate.

6. An alternating current machine according to claim 5, wherein the prongs are shaped so that the nearer sides of juxtaposed prongs converge towards the ends of the prongs remote from the back portion, the mouths formed between those ends of juxtaposed pairs of the prongs being sized such that a terminal lead can be fitted into the intervening spaces between each juxtaposed pair of prongs with a snap action.

7. An alternating current machine according to claim 5, wherein each member is provided with means fitted to the ends of its prongs for bracing the leads into it.

8. An alternating current machine according to claim 7, wherein said means which are operable to brace the leads into each member are part of an elongate flexible rod member which, in addition to functioning to brace the leads into the respective member, also comprises a strap portion which is passed under the back portion of the respective member, remote from the prongs, and under bundles of conductors that comprise portions of the stator windings that have been turned around at said one

9. An alternating current machine according to claim 1, wherein the rotor is coupled with a fan for conjoint rotation, the fan being within a casing and being operable to cause air flow through the stator from said one end, that air flow being drawn into the stator through the ventilation gaps formed between juxtaposed terminal leads and adjacent supporting and guiding means at said one end of the stator, the casing cooperating with the fan to provide a conduit for discharge air flow from the fan.

15 10. An alternating current machine according to claim
9, wherein the conduit is in the form of a volute whereby
its area increases progressively in the downstream
direction.

20 11. An alternating current machine according to claim 9, wherein there are two sets of conduits diametrically opposed one with respect to the other and oriented to discharge in opposite directions.

25 12. An alternating current machine according to claim

10, wherein the fan is a radial flow fan which has blades which project from the hub at an angle which is oblique to the radial whereby those blades trail the radial.

5 13. An alternating current machine according to claim 10, wherein the tip of each blade is angled with respect to the axis of rotation of the fan whereby it diverges from the surrounding casing wall in the direction which is parallel to the axis of rotation and which extends
10 away from said one end of the stator.

14. An alternating current machine according to claim 10, wherein the fan is bolted onto the rotor so as to be readily replaceable.

15 15. An alternating current machine according to claims 1 to 14, wherein said terminal means comprise a structural panel formed of an electrically insulating structural material, busbars which extend through and
20 which are supported by the panel with minimal clearance therearound, the busbars having terminals formed at either end, said terminal leads being connected to the busbar terminals that are on the same side of the panel as are the stator windings, the arrangement being such
25 that the panel substantially closes the surrounds of the

d which is
 nating cu
 the struc
 ongate me
 nating cu
 each elon
 ortions o
 ce to f
 between the
 ting also
 cess form
 ed angle a
 rning c
 the bush
 , for ea
 eutral an
 between
 ars from
 le selecti
 ether for
 bush of
 t output

5

10

20

25

the other busbar of each said pair to the other of the power output and neutral busbars for a parallel star connection, said connections by said linking means being made on the side of said structural panel opposite to the
5 ends of the busbars to which said terminal leads are connected.

19. An alternating current machine according to claims 1, wherein the neutral terminal leads are connected to
10 a solid ring of a good electrically conducting material which in turn is connected to said terminal means.

20. An alternating current machine according to claim 19, in which said terminal means comprise a structural panel formed of an electrically insulating structural material, busbars which extend through and which are supported by the panel with minimal clearance therearound, the busbars having terminals formed at
15 either end, said terminal leads being connected to the busbar terminals that are on the same side of the panel as are the stator windings, the arrangement being such that the panel substantially closes the surrounds of the busbars around which it is close fitted, wherein said
20 ring is connected to a neutral busbar below said panel.

5

10

15

25

each member are part of an elongate flexible rod member which in addition to functioning to brace the leads into the respective member, also comprises a strap portion which is passed under the back portion of the respective member, remote from the prongs, and under bundles of conductors that comprise portions of the stator windings that have been turned around at said one end of the stator, whereby the respective member is strapped to the stator windings by the strap position, wherein said ring is held so supported in contact with said one prong of each said member by the respective flexible rod member by which that member is strapped to the stator windings.

25. A terminal arrangement for leads from stator windings of an alternating current machine, comprising an array of structural members and busbars which extend through and which are supported by the array, the busbars having terminals at either end, wherein the improvement comprises the structural members of the array being formed of an electrically insulating structural material and being in face to face abutment whereby they form a structural panel which presents a substantially uninterrupted surface, each of the busbars which extends through and which is supported by the panel being a close fit within a respective through passage, the through

5

10

15

20

25

5

10

29. An alternating current machine according to claim 28, wherein there are two such conduits diametrically opposed one with respect to the other and oriented to discharge in opposite directions.

25

31. An alternating current machine according to claim 28, wherein the fan is bolted onto the rotor so as to be readily replaceable.

Adapt